

150-3

AECO-SOL 0070 PERMEATE AGENT

(Permeate Agent, Plastisol Ink Additives, Non-Phthalate & PVC)

Features

- Use on diluting Plastisol ink due to high viscosity or printing to sink into fabric on the purpose of print.
- Great performance as thinner, higher than Reducer.

Usage

- Usage: less than 5%

Application

- Increasing liquidity and leveling, so this enable to do Coating Print(such as Knife Coating).
- On Reverse Print
 - Mix 5~20% to let fabric can absorb ink, so print result be appear on the other side.
- Excessive usage may cause contamination around the prints, with shape like oil is spreading.

Remarks

- Stir before printing for convenient use.
- Keep cap closed tight when not in use.
- If needed to mix other product or material, contact AONE for more information.

Eco-Friendly

- Compliant with CPSIA(Pb, Phthalates).
- Meet standard of Eco-passport, adidas A-01, NIKE RSL.
- AONE's product does not contain regulated materials, but we do not examine whole product. We recommend to examine every kind of regulated materials and pre-testing for your own use purpose.

Applicable Product

- Every NP & NPP Series.

Packing & Storage

- Packaging: 15Kgs.
- Storage: Avoid strong Acidic compounds and keep in cool place(64~90°F / 18~32°C), Keep cap closed tight after use.