

150-5

AECO-SOL 0010 UR-BOND

(UR-BOND, Plastisol Ink Additives, Non-Phthalate & PVC)

□ Features

- Feature of improving adhesion and abrasiveness when mix with Plastisol ink.
- Solvent-free type, additive resin.
- Able to enhance adhesion to polyester and nylon.
- Anti-abrasive effect for Jean printing.
- Compatible with Plastisol Ink (NP & NPP SERIES), except NP-CK Series.

□ Usage

- Usage: 5~7%
- Pot-life: about 4 hours(77°F / 25°C).

□ Application

- Mix moderate amount for each work.
- Able to check adhesion after 24 hours of print, due to firmness of cross-link is increasing after 24 hours of print.
- Hard and stiff result after cross-link.

□ Remarks

- Stir before printing for convenient use.
- Keep cap closed tight when not in use.
- Conduct enough test before main printing.
- If needed to mix other product or material, contact AONE for more information.

□ Eco-Friendly

- Compliant with CPSIA(Pb, Phthalates).
- Meet standard of Eco-passport, adidas A-01, NIKE RSL.
- AONE's product does not contain regulated materials, but we do not examine whole product. We recommend to examine every kind of regulated materials and pre-testing for your own use purpose.

□ Applicable Product

- Every NP & NPP Series.
(Except NP-CK SERIES)

□ Packing & Storage

- Packaging: 20Kgs.
- Storage: Avoid strong Acidic compounds and keep in cool place(64~90°F / 18~32°C), Keep cap closed tight after use.