

150-6

AECO-SOL 0040 FAST SETTING

(Fast Setting, Plastisol Ink Additives, Non-Phthalate & PVC)

Features

- Plastisol ink additive, decreased fusion time, without affecting original feature and viscosity of ink.

Usage

- Mix rate of NP & NPP SERIES - Usage : 5~10%
(By exception, Usage of NP-FL SERIES is 2~3%. Excessive usage may increase thickness.)
- Mix rate of NP-CK SERIES - Usage : less than 5%
(Excessive usage may cause loss of crack effect.)

Application

- Adjust mix rate by checking concealment force.
- The fusion time would decrease if this additive mixed, but obey curing temperature and time of Plastisol Ink on final curing.

Remarks

- Stir before printing for convenient use.
- Keep cap closed tight when not in use.
- Conduct enough test before main printing.
- If needed to mix other product or material, contact AONE for more information.

Eco-Friendly

- Compliant with CPSIA(Pb, Phthalates).
- Meet standard of Eco-passport, adidas A-01, NIKE RSL.
- AONE's product does not contain regulated materials, but we do not examine whole product. We recommend to examine every kind of regulated materials and pre-testing for your own use purpose.

Applicable Product

- Every NP & NPP Series
(Except NP-CK SERIES).

Packing & Storage

- Packaging: 15Kgs.
- Storage: Avoid strong Acidic compounds and keep in cool place(64~90°F / 18~32°C), Keep cap closed tight after use.