

350-2

SL- AD 1910 Thickener & Matte Agent

(Thickener & Matte Agent, Silicone Ink Additives, Non-Phthalate & PVC)

Features

- Additive of Silicone ink, increase viscosity and Matte effect by mix small amount.
- Rapid increase of viscosity when mixed.
- Able to increase thixotropy of Silicone Ink and keep original shape of print.
- Liquid type, good workability.

Usage

Usage: <u>0.1~0.3%</u>

Application

- Mix 0.1~0.3% of this product on Silicone Ink and then Mix catalyst.
- After mix this product, if printed by higher mesh count, would have Matte appearance made from mark of mesh.
- If mix this product to Silicone Ink and mix catalyst, viscosity may decrease, so mix this
 product after mix catalyst to increase viscosity.

Remarks

- It is desirable to use within 6 month from manufacture date, but if passed 6 month, use
 after test of curing ability and adhesion, etc.
- Excessive usage may cause loss of elongation, tensile strength, adhesion, and lower fusion speed.
- If needed to mix other product or material, contact AONE for more information.

Eco-Friendly

- Compliant with CPSIA(Pb, Phthalates).
- Meet standard of Eco-passport, adidas A-01, NIKE RSL.
- AONE's product does not contain regulated materials, but we do not examine whole
 product. We recommend to examine every kind of regulated materials and pre-testing
 for your own use purpose.

Applicable Product

• Every SILITHANE SERIES.

Packing & Storage

- Packaging: 1Kg, 16Kgs
- Storage: Avoid direct sun, keep in cool place(41~77°F / 5~25°C), keep cap closed tight after use.

Date: MAT 1. 2